

TSW304

DIN RAIL ETHERNET SWITCH



TSW304 360° VIEW

TSW304 is the tiniest Ethernet switch in the Teltonika Networks portfolio, made with the industrial application scenarios in mind. This ultra-small device comes with an integrated DIN rail mounting option and will easily find its place in any server cabinet. Durable design and shock-resistant casing make it perfect for even the most challenging industrial environments.



MOUNTING

Integrated DIN rail bracket

COMPACT


102 x 25 x 81.5 mm

GIGABIT ETHERNET

4 x Gigabit Ethernet with speeds of up to 1000 Mbps

7-57 VDC / 9-40 VAC

Wide range of supported power supply voltages



KEY FEATURES

HARDWARE

Powering option	2-pin power socket, 7 - 57 VDC / 9 - 40 VAC
Power consumption	Idle: < 0.26 W, Max: < 1.44 W
Ethernet	4 x 10/100/1000 Ethernet ports
Status LEDs	8 x Ethernet, 1 x Power
Ingress protection rating	IP30
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with wall or DIN rail mounting option and grounding capability
Installation	DIN Rail mountable (no additional kit needed)

PERFORMANCE SPECIFICATIONS

Dimensions	102 x 25 x 81.5 mm
Weight	210 g
Bandwidth	8 Gbps
Packet buffer	128 KB
Jumbo frame support	9216 bytes
MAC address table size	2K entries
Auto MDI/ MDI-X Cable Detection	Yes

FRONT VIEW**BACK VIEW**